

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

#12/A 4-11-03 Rubertz Conclt

Applicants:

Stanek, et al.

Appl. No.:

09/864,972

Conf. No.:

3436

Filed:

May 25, 2001

Title:

DIAGNOSTIC BLOWN FUSE INDICATOR

Art Unit:

2835

Examiner:

Vortman, Anatoly

Docket No.:

112690-045

Commissioner for Patents Washington, DC 20231

RESPONSE TO OFFICE ACTION

Sir:

In response to the Office Action dated October 30, 2002, and the telephone interview courteously granted to Applicants' representative on Feb. 3, 2003, please amend the above-identified patent application as follows:

In the Specification:

Please amend the paragraph beginning at page 5, line 13 as follows:

RI

In an embodiment, the short circuit indicator and the current overload indicator electrically communicate with an end cap of the fuse.

In the Claims:

Please amend Claim 1 as follows:

br

- 1. (Amended) A diagnostic blown fuse indicator for a fuse having both a short circuit element and a current overload element, comprising:
- a short circuit indicator in electrical communication with the short circuit element, wherein the short circuit indicator provides visual indication of a short circuit condition;
- a current overload indicator in electrical communication with the current overload element, wherein the current overload indicator provides visual indication of an overload condition;

04/09/2003 HABDELR1 00000105 09864972

01 FC:1201 02 FC:1202